

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:

Brian Douglas Fiut, et al.

Serial No. Unassigned

Filed: Herewith


For: INTEGRATION OF REMOTE MICROCELL  
WITH CDMA INFRASTRUCTURE

Attorney Docket No.: SBC 0112 PA (A00432)

I hereby certify that this correspondence is being deposited with the United States Postal Service as "Express Mail" under Label No. EL817594044US in an envelope addressed to: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231 on:

December 13, 2001  
Date of Deposit

Angie Moscovitz

  
Signature

**PRELIMINARY AMENDMENT**

Assistant Commissioner for Patents  
Box Patent Application  
Washington, D.C. 20231

Sir:

Prior to the examination of the above-identified continuation application, please enter the following amendment.

**In The Specification:**

On Page 1, before the first line, please add the following:

**CROSS-REFERENCE TO RELATED APPLICATIONS**

This is a continuation of United States Patent Application  
Serial No. 09/088,506 filed on June 1, 1998.

10022147 "121301  
FOELET" 2422001

**In The Abstract:**

Please amend the abstract to read as follows:

An integrated microcellular communication system and a CDMA communication system having signal advancing capabilities wherein a signal is advanced to compensated for the time delay induced by communication signal travel over a fiber optic connections between a base station cellsite and a remote microcell.

**In The Claims:**

Please add the following new claims 14-22.

14. (New) A microcellular communication system integrated with a code division multiple access communications system comprising:

a microcellular communication system having at least one remote;

a code division multiple access (CDMA) communications system comprising:

a base station in communication with said at least one remote;

at least one face in communication with said base station; and

signal advancing capability;

means for measuring a fiber length of optical fiber connections between said base station and said at least one remote microcell in said CDMA communications system;

means for measuring a loss in said fiber optic connections;

means for measuring remote power output of said at least one remote microcell;

means for calculating an advance of a CDMA signal;

means for translating said calculations to a database for advancing said signal allowing said at least one remote to communicate with said at least one face; and

means for setting output levels of said CDMA system from said calculations.

15. (New) The integrated system as claimed in claim 1 further comprising means for testing said integrated system for proper operation.

16. (New) The integrated system as claimed in claim 1 wherein said microcellular communications system further comprises a stand-alone microcellular communications system.

17. (New) The integrated system as claimed in claim 3 further comprising hardware for interconnecting said at least one remote and said at least one face.

18. (New) The integrated system as claimed in claim 4 further comprising:

a combiner for each face to be integrated;

a meter connected to said CDMA system for measuring output power at said at least one face;

a transmit cable connected between each of said combiners;

a receive cable connected to each of said combiners;

a termination for each of said receive cables.

19. (New) The integrated system as claimed in claim 1 wherein said microcellular communication system further comprises a simulcast microcellular communication system.

20. (New) The integrated system as claimed in claim 6 further comprising hardware for interconnecting said at least one remote and said at least one face.

21. (New) The integrated system as claimed in claim 7 further comprising:

- a transmit cable connected to each of said at least one faces;

- a combiner connected to each of said transmit cables;

- an interface module for said remote wherein each of said transmit cables are connected to said interface module;

- a receive cable connected between said interface module and said at least one face;

- a combiner connected to said receive cable; and

- an attenuator connected to said combiner and said receive cable.

22. (New) The integrated system as claimed in claim 1 wherein said microcell communication system further comprises a transmit antenna and a receive antenna and said means for calculating an advance of said CDMA signal further comprises:

- means for calculating propagation delay of said transmit antenna;

means for calculating propagation delay of said receive antenna;

means for selecting a lowest value of said propagation delay for both said transmit and said receive antennas;

means for recording said selected lowest values;

means for calculating a maximum differential of all delay calculations for said remote;

means for calculating a sector size of said face;

means for calculating a search window size for said face being integrated with said remote;

means for calculating an actual input analog composite power on said face being integrated with said remote;

means for calculating a total gain for said at least one remote;

means for calculating an actual gain for said at least one remote; and

means for calculating CDMA input power for said at least one remote.

Respectfully submitted,

**ARTZ & ARTZ, P.C.**



Angela M. Brunetti  
Reg. No. 41,647  
28333 Telegraph Road, Suite 250  
Southfield, MI 48034  
(248) 223-9500

Dated: December 13, 2001

**"VERSION WITH MARKINGS TO SHOW CHANGES MADE"**

**In The Specification:**

On Page 1, before the first line, please add the following:

**CROSS-REFERENCE TO RELATED APPLICATIONS**

This is a continuation of United States Patent Application  
Serial No. 09/088,506 filed on June 1, 1998.

**In The Abstract:**

Please amend the abstract to read as follows:

[A method of interconnecting] An integrated  
microcellular communication system and a CDMA [cellsite]  
communication system having signal advancing capabilities [with  
at least one remote microcell without re-synchronization  
capabilities. The method of the present invention sufficiently  
advances the signal to compensate] wherein a signal is  
advanced to compensated for the time delay induced by  
communication signal travel over a fiber optic connections  
between a base station cellsite and a remote microcell.

**In The Claims:**

Please add the following new claims 14-22.

14. (New) A microcellular communication system  
integrated with a code division multiple access communications  
system comprising:

a microcellular communication system having at least  
one remote;

a code division multiple access (CDMA)  
communications system comprising:

10022147 124304  
FOIEU 4/22/01

means for setting output levels of said CDMA system  
from said calculations.

16. (New) The integrated system as claimed in claim  
rein said microcellular communications system further  
prises a stand-alone microcellular communications system.

17. (New) The integrated system as claimed in claim 3 further comprising hardware for interconnecting said at least one remote and said at least one face.

18. (New) The integrated system as claimed in claim 4 further comprising:

a combiner for each face to be integrated;

a meter connected to said CDMA system for measuring output power at said at least one face;

a transmit cable connected between each of said combiners;

a receive cable connected to each of said combiners;

a termination for each of said receive cables.

19. (New) The integrated system as claimed in claim 1 wherein said microcellular communication system further comprises a simulcast microcellular communication system.

20. (New) The integrated system as claimed in claim 6 further comprising hardware for interconnecting said at least one remote and said at least one face.

21. (New) The integrated system as claimed in claim 7 further comprising:

a transmit cable connected to each of said at least one faces;

a combiner connected to each of said transmit cables;

an interface module for said remote wherein each of said transmit cables are connected to said interface module;

10022147-131301



a receive cable connected between said interface module and said at least one face;

a combiner connected to said receive cable; and

an attenuator connected to said combiner and said receive cable.

22. (New) The integrated system as claimed in claim 1 wherein said microcell communication system further comprises a transmit antenna and a receive antenna and said means for calculating an advance of said CDMA signal further comprises:

means for calculating propagation delay of said transmit antenna;

means for calculating propagation delay of said receive antenna;

means for selecting a lowest value of said propagation delay for both said transmit and said receive antennas;

means for recording said selected lowest values;

means for calculating a maximum differential of all delay calculations for said remote;

means for calculating a sector size of said face;

means for calculating a search window size for said face being integrated with said remote;

means for calculating an actual input analog composite power on said face being integrated with said remote;

means for calculating a total gain for said at least one remote;

means for calculating an actual gain for said at least one remote; and

10022147 " 121301

means for calculating CDMA input power for said at  
least one remote.

10022147 434304